



CAPITAL CONTROLS

Capital Controls Series FX4800/4900 gas feeders are floor cabinet mounted, vacuum operated and designed to conveniently house a combination of gas feed equipment and controls. The cabinets enclose the gas flow control components and are constructed of ABS with a textured, easily maintained finish.

Easy to install for indoor installation, each Series FX4800/4900 cabinet is factory tested and needs no field adjustment prior to start-up. Eleven different flowmeter capacities ranging from 10 to 8,000 PPD (200 g/h to 150 kg/h) provide versatility in meeting gas flow requirements.

Manual Series FX4800 gas feeders consist of a cabinet, vacuum regulator and an ejector, or chemical induction unit. When automatic control is required (Series FX4900), Capital Controls' automatic valve, mounted in the cabinet responds to control signals from the CAPTROL[®] controller. The controller receives signals from a water flow transmitter and/or chlorine residual analyzer. If multiple feed points are required, remote meter panels and additional ejectors are provided. A switchover module is offered to provide for uninterrupted service.

ADVANCE[™] Gas Feeders Series FX4800/4900



- ◆ Worldwide standard for gas feeder technology
- ◆ Safe, reliable all-vacuum operation
- ◆ New, improved, textured design
- ◆ Front access to internal components
- ◆ Superior materials of construction
- ◆ Variable capacities up to 8,000 PPD (150 kg/h)
- ◆ Microprocessor based automatic controls
- ◆ Accurate gas metering of chlorine; sulfur dioxide
- ◆ Versatile vacuum regulator mounting
- ◆ Automatic switchover gives uninterrupted service

Applications

For process water, waste treatment and water treatment in the municipal or industrial marketplace

- ◆ **Disinfection:** potable water, municipal wastewater
- ◆ **Chloramination:** potable water
- ◆ **Dechlorination:** textiles, wastewater effluent
- ◆ **Cooling water:** control of slime and algae in piping, heat exchangers and cooling towers
- ◆ **Irrigation systems:** slime and algae control
- ◆ **Process water:** chemical and pharmaceutical manufacture, food (washdown, canning, bleaching, taste and odor control)
- ◆ **Cyanide, chromium removal:** metal finishing wastes
- ◆ **Zebra mussel control**

Design Features

- ◆ **Modern Design:** Superior materials of construction provide durability, textured finish resists fingerprints and dirt.
- ◆ **Reliable:** All vacuum operation, integral venting system, double-thickness main regulating diaphragm.
- ◆ **Safe:** Remote vacuum regulator mounting enhances safety of installation.
- ◆ **Versatile:** Cylinder, ton container, wall or manifold vacuum regulator mounting in units up to 500 PPD (10 kg/h). Unit can be provided as manual or with automatic control. Variety of ejectors available for all applications.
- ◆ **Automatic Switchover:** A separate, independent vacuum operated device that does not require manual reset. Each vacuum regulator has flow indication, a separate independent vent and an integral pressure relief device.
- ◆ **Technologically Advanced:** The CAPTROL® controller provides microprocessor-based control, fully field configurable with gas flow output signal. The controller accepts a signal from the flow sensor and/or residual analyzer. An automatic linearized gas feeder control valve is provided for reliable control.
- ◆ **Ease of installation:** Simplicity of design and modularized components minimize installation time.

- ◆ **Convenient:** Controls are located at eye level and are front panel adjustable, with an easily removable front bezel for access to internal components. Saves valuable floor space in new and existing facilities.

Operation

Vacuum Regulator

Water flowing through the ejector venturi, creates a vacuum which opens the check valve in the remote ejector. The vacuum is carried through the vacuum line to the vacuum regulator where the differential pressure causes the inlet valve on the vacuum regulator to open, initiating gas flow. A spring opposed diaphragm in the vacuum regulator, regulates the vacuum. The gas passes under vacuum through the cabinet mounted flowmeter and rate control valve. A differential pressure regulator (for automatic systems and 2000 PPD/40 kg/h and above systems) maintains a constant differential across the rate control valve. Gas flows through the vacuum line and to the ejector where the gas is thoroughly mixed with the water and applied as a solution. (Figure 1)

The system is completely under vacuum from the ejector to the vacuum regulator inlet safety valve. If the water supply to the ejector stops or vacuum is lost for any reason, the spring loaded inlet safety valve immediately closes and isolates the pressure gas supply. If the gas source depletes, the unit

seals to prevent moisture from being drawn back into the gas source. When more than one feed point is desired multiple flowmeters and ejectors can be supplied.

For uninterrupted gas feeding on a round-the-clock basis, an automatic switchover system is provided (up to 4000 PPD [75 kg/h]). Gas flows under vacuum from the regulator in service until that source is depleted, then the switchover module automatically switches service to the standby source. The standby supply will not be accessed until the supply in service is exhausted.

Chemical Induction Units

Capital Controls CHLOR-A-VAC® Series 1420 chemical induction units offer improved chlorination and dechlorination through the high-efficiency mixing of gaseous chemical with process water. This translates into operating and chemical cost savings.

CHLOR-A-VAC® units produce a vacuum when process water passes through water inlet ports and through a venturi. The high vacuum and recessed impeller create great turbulence and complete chemical mixing.

A chemical induction unit in lieu of an ejector should be considered for the following applications: contact basins, headwater, return sludge processes, clarifier inlets, collection basins, equalization tanks and clear wells. (See Bulletin 130.0001)

Automatic Control

For variable flow and demand conditions, automatic gas flow control is recommended. An automatic valve is provided to open and close in proportion to a signal received from the controller (Figure 2). The controller receives electrical input signals from a flow meter and/or residual analyzer, causing the controller to automatically reposition the control valve to maintain the desired gas feed rate or chlorine residual.

Automatic floor cabinet units include: controller, automatic linear gas feeder control valve with electronic manual adjustment switch, manual bypass valve and differential pressure regulator. Controller may be remote mounted.

The CAPTROL® microprocessor controller is field configurable for three chlorination and two dechlorination control modes:

- ◆ **Flow:** Proportioning valve position to process flow.
- ◆ **Residual:** Single, integral action, opening valve based on residual set point.
- ◆ **Compound Loop:** Simultaneous proportioning valve position to a combination of flow proportioning and residual control. If one signal is lost, the controller automatically proportions based on remaining signal.
- ◆ **Feed Forward:** Valve position control directly proportional to flow signal multiplied by residual signal, provided by built-in multiplier.

Technical Data ADVANCE™ Gas Feeders

GENERAL

Capacities: Standard metering tubes are available with the following capacities 10, 25, 50, 100, 200, 500, 1000, 2000, 4000, 6000 and 8000 PPD (200 g/h, 0.5, 1, 2, 4, 10, 20, 40, 75, 120, and 150 kg/h) of chlorine gas.

To determine feed rates for other gases, multiply each chlorine value by:

0.95 for sulfur dioxide

0.50 for ammonia

0.78 for carbon dioxide

Flowmeter: The minimum feed capacity for every gas flowmeter is 1/20th of the maximum capacity for manual units 1/10th of maximum capacity for automatic units.

Accuracy: Within ±4% of maximum flowmeter capacity.

Electrical Requirements: 120/240 Vac, 60/50 Hz, single phase

Dimensions: 54 3/4"(1391 mm) H X 22 3/4(578 mm) W X 12 3/4" (324 mm) D

Model Information Code

Model F X 4
Floor Cabinet Gas Feeder

Control Mode

80 - Manual

94 - Automatic

Capacity (Chlorine)

1 - 100 PPD (2 kg/h)

2 - 200 PPD (4 kg/h)

3 - 500 PPD (10 kg/h)

4 - 2000 PPD (40 kg/h)

5 - 8000 PPD (150 kg/h)

Gas

C - Chlorine

S - Sulfur Dioxide




Figure 2 - Automatic Gas Feed System

Warranty and Capability

Capital Controls offers a one (1) year limited warranty on Series FX4800/4900 equipment.

Capital Controls is ISO 9001 certified to provide quality and precision materials. Disinfection technologies, water quality monitors and instrumentation for water and wastewater are areas of specialization. Over 35 years of industrial and municipal application experience in the water and wastewater industries is incorporated into the equipment design to provide high quality comprehensive solutions for the global market.

Brief Specification

The floor cabinet mounted gas feeder shall be provided with a maximum capacity of 8,000 PPD (150 kg/h) chlorine gas per day. The gas feeder shall be vacuum operated and shall convey the gas under vacuum from the vacuum regulator to the ejector/check valve assembly to maintain complete system safety.

The gas feeder shall be housed in a floor cabinet of pressure formed plastic and structural foam plastic construction. The cabinet front shall be removable to permit access to the internal components. All utility inlets and outlets shall be bulkhead connections mounted in the rear and all electrical connections shall be made to one terminal box. The cabinet shall house a dual scale (English/metric) gas flowmeter and an automatic control valve and be sized for an operating maximum capacity of 8,000 PPD/150 kg/h. The cabinet shall also include a manual gas flow control valve, differential pressure regulator, and vacuum gauge. The automatic controller shall be remote mounted from the floor cabinet.

All components carrying gas shall be made of materials suitable for wet or dry gas service. All springs shall be of tantalum alloy, the automatic valve plug shall be of materials suitable for the specified gas.

Design improvements may be made without notice.

Represented by:



CAPITAL CONTROLS

3000 Advance Lane Colmar, PA 18915
Tel: 215-997-4000 • Fax: 215-997-4062
Web: www.capitalcontrols.com
E-mail: marketing@capitalcontrols.com

- UNITED KINGDOM • UNITED STATES • HONG KONG
- INDIA • ITALY • MALAYSIA